

Memorandum Planning & Development Services Division

To:

Planning and Public Works Committee

From: John Boyer, Senior Planner

Date: March 21, 2013

RE: <u>**T.S.P. 41-2013 T-Mobile (731 Spirit 40 Park Drive):**</u> A request to obtain approval to amend a Telecommunications Siting Permit to accommodate six (6) additional antennas as well as new ground equipment on an existing monopole tower within the "M3" Planned Industrial District of land located north of the intersection of Spirit 40 Park Drive and Chesterfield Airport Road (17V420146).

Summary

Aaron Adelman (applicant) has submitted a request for a Telecommunications Siting Permit (TSP) for the above referenced property (see Figure 1 for location of existing tower). The proposed TSP is to accommodate six (6) new antennas as well as associated new ground equipment for an existing site. The antennas are planned to be located on an existing antenna platform of the tower located 100 feet above surrounding grade. No antennas are planned for removal with this application (only additions). The additional ground equipment will be installed within the existing enclosure around the tower (see Figure 2 below for picture of existing site).



Figure 1: Location Map



Figure 2: Site Photo

History

The subject property is lot #3A of the Spirit 40 Park Lots 3 & 4 Boundary Adjustment subdivision and is zoned "M3" Planned Industrial District. The tower was approved by the City of Chesterfield in April of 2000 as a 100 foot tall monopole. In 2009, TSP 09-2009 was requested and approved for the replacement of three (3) antennas and associated ground equipment for an antenna upgrade.

Discussion

City Code requires that ground equipment be fenced to mitigate unauthorized access. The existing ground equipment is fenced and additionally screened from adjacent properties by an existing sight proof wall surrounding the site (see Figure 2).

City of Chesterfield Ordinance #2391, which governs telecommunications and facilities siting, permits applications for equipment upgrades to be submitted for sites that currently hold a

Telecommunications Siting Permit (TSP) without the need for a public hearing. Staff has reviewed the



request by T-Mobile and has determined that the proposed addition of six (6) antennas as well as additional ground equipment to an existing and permitted site may amend the existing permit without the need for a public hearing.

Attached please find a copy of the statement of intent, construction plans, and site plan of the site.

Respectfully submitted,

John Boyer Senior Planner

cc. Aimee Nassif, Planning & Development Services Director





March 13, 2013

City of Chesterfield Planning & Development Division 690 Chesterfield Parkway West Chesterfield, MO 63017-0760

STATEMENT OF INTENT

RE: T-Mobile's Proposed Antenna Upgrades at 471 North Woods Mill Road, Chesterfield, MO, 63017-3238 RE: T-Mobile's Proposed Antenna Upgrades at 731 Spirit 40 Park-A, Chesterfield, MO, 63005-1142

Dear Madam or Sir,

T-Mobile has leased space at the wireless communication site located at <u>471 North Woods Mill Road</u> and 731 Spirit 40 Park-A. T-Mobile is in the process of upgrading their existing equipment with new technology to replace their existing obsolete technology. This is being done to support their 4G Network.

For <u>731 Spirit 40 Park Drive</u>, T-Mobile currently has 3 antennas on their array at 100'. They propose to add 6 more antennas at the same height. No antennas are being removed.

For <u>471 North Woods Mill Road</u>, T-Mobile currently has 3 antennas on their array at 90'. They propose to add 6 more antennas at the same height. No antennas are being removed.

Per the structural analysis conducted at each site, both structures are designed to accommodate the proposed load.

No additional cabinets or structures will be erected at the site. Any new equipment will be mounted to the pedestal next to the existing equipment cabinet.

T-Mobile's installation is a collocation upgrade and will <u>not</u> extend the height of the structure. T-Mobile will <u>not</u> be expanding the existing fenced compound. T-Mobile will <u>not</u> be adding any lighting to the tower.


This installation will <u>not</u> change the existing use of the Wireless Communication Tower.

Respectfully,


Aaron Adelman SMJ International, LLC


VICINITY MAP	PROJECT INFOR	RMATION					
	PROJECT ADDRESS: 737 SPIRIT 40 PARK DRIV CHESTERFIELD, MISSOU		SHEET NUMBER T-1 TITLE SHEET	LE DESCRIPTION	REVISION 0	RESPONSIBLE DISCIPLINE SC/E	AMERICAN TOWER
SITE	INFORMATION: LONGITUDE: -90 TOWER HT: 10	.67216882 N 0.6416901 W 0'-0" AGL 0'-0" AGL	A-1 SITE PLAN A-2 CONDUIT LAYOUT A-3 EQUIPMENT BLEV A-4 TOWER ELEVATIO		0 0 0	SC SC SC SC	3200 COBB GALLERIA PARKWAY, SUITE : ATLANTA, GEORGIA 30339 PHONE: (770) 308-1973
	APPLICANT: T-MOBILE 2004 WESTPORT CENTER ST. LOUIS, MISSOURI 631	DRIVE	A-5 ANTENNA, RRU & A-6 NSN CONFIGURAT A-7 RRU CONNECTION	TMA CONFIGURATION KEYS		SC SC SC SC SC	T - Mobile
THE STREET	CONSULTING	G TEAM	G-1 GROUNDING PLAN G-1 GROUNDING DET		0	E E	ST. LOUIS, MO 63148 PHONE: (314) 812-3600 FAX: (314) 812-3692
The start of the	ENGINEER: SSC, INC. 721 EMERSON ROAD, ST. LOUIS, MISSOURI PHONE: (314) 993-1010	63141	SP-1 SPECIFICATIONS (SP-2 SPECIFICATIONS (SP-3 SPECIFICATIONS (2 OF 3)	0 0 0	SC E E	
AREA MAP	FAX: (314) 993-1036 ML. OWENS - LEAD F	ENGINEER	n l	/			
	S.D. KEISLING - LEAD F. GUY - LEAD DESIG			King Juli	OF		9900 West 109th Street, Suite 300 Overland Park, Kansas 66210 Phone: 913-438-7700 Fax: 913-438-777
	PROJECT MANAGER: CHUCK HALL AMERICAN TOWER O PHONE: (314) 575-0000		MICHAEL L WENS	*	SHELTON	CP	STATE OF <u>MISSOURI</u> CERTIRCATE OF AUTHORIZATION 1001640 RESPONSIBLE ENGINEERS: RESPONSIBLE DISCIP KV KERN VANAMELE: 21561 STRUCTURALCOML KU MCMMUNATELE: 22066 STRUCTURALCOML
LOCATION AND AND AND AND AND AND AND AND AND AN	APPROVA	ALS	₩ <u>₩</u>		E 2732		REJ ROBERTE JENSIM PECOSSPI ATRUCTURAUCOM SDK SHELTON D KEISUNG E-27723 ELECTRICAL THIS TERRANCE M SUPER E-18521 ELECTRICAL
	SSC	DATE		1// 6/13	IONAL E	····	DESIGNER: F. GUY
	RF	DATE		Anh	OT		LEAD EE: S.D. KEISLING LEAD CE/SE: M.L. OWENS
	T-MOBILE	DATE		VIUU USA,		C. C. C.	SUBMITTALS NO. DATE DESCRIPTION A 01/10/13 ISSUED FOR REVIEW 0 01/15/13 ISSUED FOR CONSTRUCTION
DRIVING DIRECTIONS DRIVE TO DIRECTIONS AS FOLLOWS:	OPERATIONS	DATE		PGRADE	-		
FROM T-MOBILE OFFICE AT PAGE AVENUE AND WESTPORT CENTER DRIVE. TAKE PAGE AVENUE WEST (1.4) TO 1-270 SOUTH. TAKE 1-270 SOUTH (4.1 MI) TO 1-64/US-40 EXIT. 12. TAKE 1-64/US-40 WEST (9.4) TO CHESTERFIELD AIRPORT ROAD	REAL ESTATE	DATE		NG CELL			SITE NAME
KEEP STRAIGHT ONTO LONG ROAD (174 YDS) TURN RIGHT (WEST) ONTO CHESTERFIELD AIRPORT ROAD (1.6 MI) TURN RIGHT (NORTH) ONTO SPIRIT OF ST. LOUIS BLVD (0.3 MI) TURN RIGHT (EAST) ONTO N. OUTER FORTY DRIVE (0.2 MI)	EQUIPME	NT		SITE NAME:	ty of Che	sterfield	SITE NUMBER
TURN RIGHT (SOUTH) ONTO LOCAL ROADS (0.2 MI) ARRIVE AT SITE.	EQUIPMENT_FURNISHED_AND/OR DESCRIPTION FURNISHED	INSTALLED	CDU		FEB 19	The street.	MO-06-205-A
CODE COMPLIANCE	ANTENNAS T-MOBILE FLEXI STACK EQUIPMENT T-MOBILE COAX HANGERS CONTRACTOR	CONTRACTOR TWOBILE CONTRACTOR	SPI	KII 40 RAR	e of Pu	ublic Servic	SITE ADORESS 737 SPIRIT 40 PARK DRIVE CLIESTERFIELD, MISSOUR 63005
ALL WORK SHALL BE PERFORMED AND MATERIALS INSTALLED IN ACCORDANCE WITH THE CURRENT EDITIONS OF THE FOLLOWING CODES AS ADOPTED BY THE LOCAL GOVERNING AUTHORITIES, NOTHING IN THESE PLANS IS TO BE CONSTRUED TO PERMIT WORK NOT CONFORMING TO THESE CODES.	CONNECTORS T-MGBILE LDF4 ANTENNA JUMPERS T-MOBILE	CONTRACTOR	}	TE NUMBER:			SHEET TIYLE
1. INTERNATIONAL BUILDING CODE 2. INTERNATIONAL MECHANICAL CODE 3. ANSI/TIA-222 STRUCTURAL STANDARD	HYBRIO CABLE T-MOBILE UPPER & LOWER COVP'S T-MOBILE RRU'S T-MOBILE	CONTRACTOR CONTRACTOR CONTRACTOR		O-06-205-A			SHEET NUMBER
4. NFPÁ 780 — LIGHTNING PROTECTION CODE 5. UNIFORM PLUMBING CODE 6. NATIONAL ELECTRICAL CODE			ATC S	ITE NUMBER:	: 9316	1	T-1


.



SITE PLAN








EQUIPMENT ELEVATION



6-0-3

8

4"



ANTENNA								FY!			AND COA	RADIATION			ANTENNA			HYBRID	HYBRID	EXISTING COAX	FINAL HYBRIG	อ
MARK	MARK	STATUS	TECH		ENNA MODE	L	ANTENNA VENE		TH TN AZIMUTH TI		DOWNTILT	CENTER	SECTOR	CONNECTOR	DIMENSIONS	TOTAL WEIGHT	HYBRIO MODEL	SIZE	LENGTH	CABLE COUNT		
A1	A	PROPOSED	LTE	тмв	XX-6516-4	A2M	ANDREW	;	50 30	0	TBD	100'-0"	Tx1/Rx	7/16 DIN	59.6"Hx12"Wx6.5") 34.6 LBS.	LOW CAPACITY HCS	1.24"	150'		1	
A2	A	EXISTING	UMTS AWS	APXV1	8-2065175	- A 20	RFS	;	30° 30°	0	2	" 0- "001	Tx2/Rx	7/16 DIN	72"Hx6.8"₩x3"D	26.4 LBS.			-	2		
A3	A	PROPOSED	UMTS/GSM PC	S TMB	XX6516-A	42M	ANDREW		sor 30°	D	2	100'0"	Tx3/R×	7/16 DIN	59.6"Hx12"Wx6.5"	34.6 LBS.	SHARED	SHARED	SHAREO	2 LMU	SHARED	3200 COBE
					·																	_
B1	<u> </u>	PROPOSED	LTÉ		XX-6516-A		ANOREW	1	50 150	0	TBD	100'-0"	Tx1/Rx	7/16 DIN	59.6"Hx12"Wx6.5"	34.6 LBS.	SHARED	SHARED	SHARED		SHARED	
82	8	EXISTING	UMTS AWS		8-2065175		RFS	_	50' 150'	0	2	100'-0"	Tx2/R×	7/16 OIN	72"Hx6.8"Wx3"0	26.4 LBS.		-	-	2		-
83	B	PROPOSED	ints/gsn pc	S TMB	XX6516-A	12M	ANDREW		50 150	0	2	100'-0"	Tx3/Rx	7/16 DIN	59.6"Hx12"Wx6.5"	34.6 LBS.	SHARED	SHARED	SHARED	2 LMU	SHARED	- T.
		PROPOSED						_														, T
C1 C2	с с	EXISTING	LTE		XX-6516-A		ANDREW		707 2705	, °	TBD	100'-0"	Tx1/Rx	7/16 DIN	59.6"Hx12 ₩x6.5"		SHARED	SHARED	SHARED		SHARED	- 2004
			MITS AWS		8-206517S 		RFS ANOREW		70° 270° 70° 270°	0	'''''''	100'-0" 100'-0"	Tx2/Rx Tx3/Rx	7/16 DIN 7/16 DIN	59.6"Hx12"Wx6.5"	26.4 LBS.		- CUADED	-	2 2 LMU	SHARED	-
	<u> </u>			AND OVP			ANUKEW	2	2/0	<u> </u>							SHARED	SHARED	SHARED			-
					OTY PER					<u>├ - </u>	- ×	<u> </u>	<u> </u>		CODING CON			CUAX C		ENTIFICATIO	<u>N</u>	-
EQUIPMENT	STATUS	S PART N	UMBER	VENDOR	SECTOR	DIN	MENSIONS	WEIGHT	TOTAL.	SECTOR	COLOR	ANTE	NNA	REFERENCE		FUNCTION				NTIFICATION AND THE FOLLOWING		<u>~ · · · · · · · · · · · · · · · · · · ·</u>
ТМА	EXISTIN	G ATMAA141	2D-1A20	RFS	1	12"H	1×10"W×4"0	13 LBS	3 AT ANTENNA LEVEL	ĹĹ	1 RED	A	1	MAJN LTE	Tx	I/R× LTE MAIN	INSTRUCTIONS:		-			
RAYCAP/OV	P PROPOSI	ED ASU9338	TYP OF 1)	-			-	-	1 UPPER &	ļĹ	2 RED	A	1	SECONDARY L	TE Tx3/F	x LTE DIVERSITY				DE USING COLO NOT TORN STRAI		
FRIG	PROPOSE	ED -		NOKIA	1	6.0"Hx	×16.4 "₩ ×20"D	58 LBS	3 AT ANTENNA LEVEL		3 RED	^	1	MAJN LITE	Tx	/Rx LTE MAIN	AND NOT BE	CONCEALED	IN TOWER N	ON THE COAX		
FXFB GSM- UMTS PCS FRIA	PROPOSE	ED		NOKIA		-	x17.5"\x22"D	55 LBS	2 AT ANTENNA LEVEL 3 AT	4 F	4 RED	A		SECONDARY L		X LTE DIVERSITY	WEATHERPROOF					
AWS UMTS	EXISTIN			NOKIA	1		×17.5 W×22"0	55 LBS	EQUIPMENT LEVEL	. F	5 RED	A		MAIN AWS/PC		× AWS/PCS MAIN	- GROUND LEVEL	SHALL ON	LY BE 3/4"	THE TOWER AND WIDE. USE 2"		9900 On
ESMB GSM	PROPOSE			NOKIA	-			33 LBS	EQUIPMENT LEVEL		6 RED	A		ECONDARY AWS		WS/PCS DIVERSITY	- ONLY ON LINE					Phone: 9
FSME UMTS				NOKIA			×17.5"Wx22"D	50 LBS	EQUIPMENT LEVEL	· F	7 RED	A		MAIN GSM/UM		/Rx GSM MAIN	NEAR	EST THE AN	TENNA (WHE	RETHE		81ATE OF MISS
FSMF LTE	PROPOSE	ED -		NOKIA	-	5.25 H	×17.5 ₩x22"0	33 LBS	EQUIPMENT LEVEL	1 –	8 RED	A		MAIN GSM/UM	<u> </u>		SECOND - AT	AND JUMPE		•		CERTIFICATE OF RESPONSIBLE EN
		_								i F	10 RED			ECONDARY GSM		/Rx GSM MAIN		RUCTURE. (F	OR TOWERS	ONLY).		KV KEVIN VANAM MLO MICHAEL L
										-		<u> ^ ^</u>	5 5	CONDART GOMY				R TO MGB)		5. (0031		REJ ROBERTE, J SOK SHELTON D. TMS TERRANCE
YPICAL	ANDREW	MANUFACTUR		COAX BE	CABLE TO		MUMIXAM		MAXIMUM	4 –										(A SITE WILL H DESIGNATEO IN		
	NUMBER		ND ANDRE	W CATALOG	CLEA SPACI	VR	VERTICAL HAN SPACING	GER HO	RIZONTAL HANGER SPACING	ļ	1 BLUE	В	1	MAIN LTE	Тх	/Rx LTE MAIN	- CLOCKWISE MA	NNER; THE	SECTOR IS	CLOSEST TO ZE	RO OEGREES	
1/2"	LDF4-50A	5"	20	6706-1	1/2'	~	4'-0"		4'-0*		2 BLUE	в	1	SECONDARY L	TE Tx3/R	× LTE DIVERSITY				IN 1 AND DIVER		
7/8"	LDF5-50A	10"	20	6706-2	1/2	•	4'-0"		4'-0"	l F	3 BLUE	в	1	MAIN LTE	Tx	/R× LTE MAIN	TWO ANTENNAS	PER SECTO	OR AND AS	i the air with The system gr		DESIGNER
7/8"	AVA5-50	10"	20	6706-2	1/2	-	4'-0"		4'-0"		4 BLUE	B	1	SECONDARY L	TE Tx3/R	LTE DIVERSITY	ADDITIONAL AN					LEAD EE:
-1/4*	LDF6-50A	15*	20	67063	1/2	•	4'0"		4'-0*		5 BLUE	B	2	MAIN AWS/PC	S Tx1/F	x AWS/PCS MAIN				IN 2 AND OVER		LEAD CE/
-5/8*	LDF7-50A	20"	20	6706-4	1/2	•	4'-0"		4'-0"	в	6 BLUE	B	2 S	ECONDARY AWS	PCS Tx3/Rx	WS/PCS DIVERSITY				IN 4 AND OWER		
-5/8"	AVA7-50A	20"	20	6706-4	1/2	·	4'-0*		4' —0"		7 BLUE	B	3	MAIN GSM/UM	ITS Tx1	/R× GSM MAIN	COLOR CODE	AS FOLLOWS				NO. DATE A 01/10/13
1/2"	FSJ4-50B	1-1/4"	20	6706-1	1/2		4'-0"		4'-0*		8 BLUE	B	S SE	CONDARY GSM/	/UMTS Tx3/R	GSM DIVERSITY	A SECTOR - P B SECTOR - E	BLUE				0 01/15/13
				ANTENNA	A NOTES	S					9 BLUE	B	,	MAIN GSM/UM	ITS Tx1	/Rx gsm main	D SECTOR - Y	TELLOW				
ANTERINI/	CONTRACT	OR SHALL INSURI		ANTENNA	7. MINIM		RADIUS:				10 BLUE	B	S SE	CONDARY GSM/	/UMTS Tx3/R	GSM DIVERSITY				R ORIGINAL COL		
MOUNTIN	G PIPES AR	RE PLUMB.					2" HARD LINE)	- 5"									WILL BE MARKI	ер үнтн түү	D BANDS OF	D OF TAPE, OF TAPE, EXTRA	WILL BE	
	FEEDER & Roximate.	FIBER LENGTHS	NDICATED		FSJ4-	50B (1/	2" SUPER FLEX 8" HARD LINE)) = 1-1,	/4~											ES, WHICH NOR	MALLY	SE SE
ANTENN	COAXIAL F	TEEDERS & ANTE	NA JUMPE	RS	AVA7-	50A (1-1	5/8" HARO LIN	E) = 15"			1 WHITE	C		MAIN LTE		/R× LTE MAIN	ORIENTATION OF	REE ANTEN	NA, IT IS SL	GGESTED THAT BE THAT OF LO	THE	
		ODED PER T-MO				•	SHALL RECORD	,			2 WHITE	C		SECONDARY LI			NORTHERLY DIR	RECTION.		<u></u> //		
	& 6 TO H. INTENNA.	AVE TMA, MOUNT	ED ON PIPE	_	AND P	OSTION	OF EACH ACTUA	ATOR INST	ALLED AT THE ON TO T-MOBILE.		3 WHITE	C		MAIN LTE		/R× LTE MAIN	ГОМ	TS LINES	- BAND	GREEN		1
LINES 5		NAS: TERMINATE U							ORS WITH SELF		4 WHITE 5 WHITE	C		SECONDARY LT		AWS/PCS MAIN		ifr origi	NAL COLO	R CODING		
LINES 5 BEHIND /			MUST TERM			AMATING					6 WHITE			ECONDARY AWS/		WS/PCS DIVERSITY	-	, ii	TEY	WW PAG		722.01
LINES 5 BEHIND MULTI P PORTS W THOROUG	ITH CONNECT HLY. JUMPE	ERS FROM TWA'S TIONS IN EACH SI				REMENT	TO CONFIRM/VA	LIDATE A	A "TAPE DROP" (TENNA CENTER	ř -				MAIN GSM/UM		Rx GSM MAIN	-		S. MIC	HAELL.	P III	737 SH CHEST
LINES 5 BEHIND MULTI P PORTS W THOROUG OPPOSITE	ith connec Hly, jumpe Polarizat	TONS IN EACH S	UFACTURER	's	110-100		CHT CONTRACT	OR SHALL	SUBMIT A		8 WHITE			CONDARY GSM/		GSM OMERSITY	-	E★		NENS	*=	
LINES 5 BEHIND MULTI P PORTS W THOROUC OPPOSITE CONTRAC RECOMMI	ITH CONNECT HLY, JUMPE POLARIZAT TOR MUST INDATIONS A	FOLLOW ALL MAN REGARDING THE J	NSTALLATION		LINE (ETED HE	JGHT VERIFICATIO	ON FORM	IO INC.										, 0		: <u> </u>	
LINES 5 BEHIND MULTI P PORTS W THOROUC OPPOSITE CONTRAC RECOMMI	ITH CONNECT HLY, JUMPE POLARIZAT TOR MUST INDATIONS A	FOLLOW ALL MAN	NSTALLATION	I OF	LINE (COMPL CONST	RUCTION	GHT VERIFICATIO				9 WHITE	63	, , , , , , , , , , , , , , , , , , , ,	MAIN GSM/UMT	TS Tx1	Rx GSM MAIN	1	111	NU	MBER	6	
LINES 5 BEHIND MULTI P PORTS W THOROUC OPPOSITE CONTRAC RECOMMI	ITH CONNECT HLY, JUMPE POLARIZAT TOR MUST INDATIONS A	FOLLOW ALL MAN REGARDING THE J	NSTALLATION	I OF	LINE (COMPL CONST 11. ALL FI COMMS	ETED HE RUCTION BER RUN SCOPE HI	IGHT VERIFICATION MANAGER. IS TO BE CONTA YBRID DC-FIBER	ained in R Cables	TWO					MAIN GSM/UMT		/Rx GSM MAIN GSM DIVERSITY	-		NU PE	MBER	6	
LINES 5 BEHIND MULTI P PORTS W THOROUC OPPOSITE CONTRAC RECOMMI	ITH CONNECT HLY, JUMPE POLARIZAT TOR MUST INDATIONS A	FOLLOW ALL MAN REGARDING THE J	NSTALLATION	I OF	LINE (COMPL CONSTI 11. ALL FI COMMS LOWER #RFF-	ETED HE RUCTION BER RUN SCOPE HI OVP'S 1 12MM-60	JGHT VERIFICATION MANAGER. NS TO BE CONTO YBRID DC-FIBER TO UPPER OVP 106-218-SPE	AINED IN R CABLES S MODEL	TWO		9 WHITE	C3					-	PHON	NU PE	MBER	6	ANTE CONF
LINES 5 BEHIND MULTI P PORTS W THOROUC OPPOSITE CONTRAC RECOMMI	ITH CONNECT HLY, JUMPE POLARIZAT TOR MUST INDATIONS A	FOLLOW ALL MAN REGARDING THE J	NSTALLATION	I OF	LINE (COMPL CONSTI 11. ALL FI COMMS LOWER #RFF-	ETED HE RUCTION BER RUN SCOPE HI OVP'S 1 12MM-60	ight vérificati(Manager. 15 to be cont, 18rid dc—fiber to upper ovp?	AINED IN R CABLES S MODEL	TWO		9 WHITE	C3					-	PKO	NU PE	MBER	6	

...





AMERICAN TOWER

3200 COBB GALLERIA PARKWAY, SUITE 205 ATLANTA, GEORGIA 30339 PHONE: (770) 308-1973

T-Mobile

2004 WESTPORT CENTER DRIVE ST. LOUIS, MO 63146

PHONE: (314) 812-3600 FAX: (314) 812-3692



9900 Wesl 109th Streel, Suite 300 Overland Park, Kansas 66210 Phone: 913-438-7700 Fax: 913-438-7777

TATE OF MISSOURI ERTIFICATE OF AUTHORIZATION 1001540 ESPONSIBLE ENGINEERS: RESPONSIBLE DISCIPLINE:

VX KEMIN VANIMABLE ELSISSI ISTRUCTURALLOVILE VX KEMIN VANIMABLE ELSISSI ISTRUCTURALLOVILE ISG NILO MICHAEL LOWENS E-SISSI ISTRUCTURALLOVIL ISG REFLEXEN IN DESISLIN E-SIZSI ISTRUCTURALLOVIL ISG SK SHELTON IN DESISLIN E-SIZZI ELECTRICAL EMIS TERRANCE M SUPER E-18521 ELECTRICAL E

F. GUY DESIGNER:

S.D. KEISUNG

SUBMITTALS O. DATE DESCRIPTION A 01/10/13 ISSUED FOR REVIEW 0 01/15/13 ISSUED FOR CONSTRUCTION BY FG DSH

M.L. OWENS

SITE NAME

SPIRIT 40 PARK

SITE NUMBER

MO-06-205-A

SITE ADDRESS


737 SPIRIT 40 PARK DRIVE CHESTERFIELD, MISSOURI 63005


SHEET TITLE


ANTENNA, RRU & TMA CONFIGURATION KEYS


SHEET NUMBER

















SECTION 16000 ELECTRICAL

PART 1 GENERAL

1.1 GENERAL CONDITIONS:

- A THE CONTRACTOR SHALL INSPECT THE SITE WHERE THIS WORK IS TO BE PERFORMED AND FULLY FAMILLARIZE HIMSELF WITH ALL CONDITIONS RELATED TO THIS PROJECT.
- B. THE CONTRACTOR SHALL OBTAIN AND PAY FOR ALL PERMITS AND LICENSES AND SHALL MAKE ALL DEPOSITS AND PAY ALL FEES REQUIRED FOR THE PERFORMANCE OF WORK UNDER THIS SECTION.
- C. DRAWINGS SHOW THE GENERAL ARRANGEMENT OF ALL SYSTEMS AND COMPONENTS COVERED UNDER THIS SECTION. THE CONTRACTOR SHALL VERIFY ALL DIMENSIONS. DRAWINGS SHALL NOT BE SCALED TO DETERMINE DIMENSIONS.

1.2 LAWS. REGULATIONS. ORDINANCES. STATUTES AND CODES.

A ALL WORK SHALL BE INSTALLED IN ACCORDANCE WITH THE NATIONAL ELECTRICAL CODE, AND ALL APPLICABLE LOCAL LAWS, REGULATIONS, ORDINANCES, STATUTES AND CODES.

1.3 REFERENCES:

A THE PUBLICATIONS LISTED BELOW FORM PART OF THIS SPECIFICATION. EACH PUBLICATION SHALL BE THE LATEST REVISION AND ADDENDUM IN EFFECT ON THE DATE THIS SPECIFICATION IS ISSUED FOR CONSTRUCTION UNLESS OTHERWISE NOTED. EXCEPT AS MODIFIED BY THE REQUIREMENTS SPECIFICATION SHALL DETAILS OF THE DRAWINGS, WORK INCLUDED IN THIS SPECIFICATION SHALL CONFORM TO THE APPLICABLE PROVISIONS OF THESE PUBLICATIONS.

1. ANSI/JEEE (AMERICAN NATIONAL STANDARDS INSTITUTE)

- 2. IEEE (INSTITUTE OF ELECTRICAL AND ELECTRONICS ENGINEERS)
- 3. ASTM (AMERICAN SOCIETY FOR TESTING AND MATERIALS)

4. ICEA (INSULATED CABLE ENGINEERS ASSOCIATION)

- 5. NEMA (NATIONAL ELECTRICAL MANUFACTURER'S ASSOCIATION)
- 6. NFPA (NATIONAL FIRE PROTECTION ASSOCIATION)
- 7. OSHA (OCCUPATIONAL SAFETY AND HEALTH ADMINISTRATION)
- 8. UL (UNDERWRITER'S LABORATORIES, INC.)

1.4 SCOPE OF WORK:

- A. WORK UNDER THIS SECTION SHALL CONSIST OF FURNISHING ALL LABOR, MATERIAL AND ASSOCIATED SERVICES REQUIRED TO COMPLETELY CONSTRUCT AND LEAVE READY FOR OPERATION SYSTEMS AS SHOWN ON THE DRAWINGS AND HEREIN DESCRIBEO.
- B. ALL ELECTRICAL EQUIPMENT UNDER THIS CONTRACT SHALL BE PROPERLY TESTED, ADJUSTED, AND ALIGNED BY THE CONTRACTOR.
- C. THE CONTRACTOR SHALL BE RESPONSIBLE FOR ALL EXCAVATING, DRAINING, TRENCHES, BACKFILLING, AND REMOVAL OF EXCESS DIRT.
- D. THE CONTRACTOR SHALL FURNISH TO THE OWNER, CERTIFICATES OF FINAL INSPECTION AND APPROVAL FROM THE INSPECTION AUTHORITIES HAVING JURISDICTION.

PART 2 PRODUCTS

2.1 GENERAL:

- A. ALL ITEMS OF MATERIALS AND EQUIPMENT SHALL BE NEW, FREE FROM DEFECTS AND OF THE BEST QUALITY NORMALLY USED FOR THE PURPOSE IN GOOD COMMERCIAL PRACTICE.
- B. ALL MATERIALS AND EQUIPMENT SHALL BE ACCEPTABLE TO THE AUTHORITY HAVING JURISDICTION AS SUITABLE FOR THE USE INTENDED.
- C. ALL EQUIPMENT SHALL BEAR THE UNDERWRITERS LABORATORIES LABEL OF APPROVAL, AND SHALL CONFORM TO REQUIREMENTS OF THE NATIONAL ELECTRICAL CODE.
- D. ALL OVERCURRENT DEVICES SHALL HAVE AN INTERRUPTING RATING EQUAL TO OR GREATER THAN THE SHORT CIRCUIT CURRENT TO WHICH THEY ARE SUBJECTED, 10,000 AIC MINIMUM, VERIFY AVAILABLE SHORT CIRCUIT CURRENT DOES NOT EXCEED THE RATING OF ELECTRICAL EQUIPMENT.


2.2 MATERIALS AND EQUIPMENT:

A. CONDUIT:

- RIGID GALVANIZED STEEL CONDUIT (RGS) SHALL BE HOT-DIP GALVANIZED INSIDE AND OUTSIDE INCLUDING ENDS AND THREADS AND ENAMELED OR LACQUERED INSIDE IN ADDITION TO GALVANIZING.
- FLEXIBLE METAL CONDUIT SHALL BE GALVANIZED, ZINC-COATED STEEL, PVC COATED FOR OUTDOOR APPLICATIONS.
- 3. CONDUIT CLAMPS, STRAPS AND SUPPORTS SHALL BE STEEL OR MALLEABLE IRON. ALL FITTINGS SHALL BE COMPRESSION TYPE AND WATERTIGHT.
- 4. NON-METALLIC CONDUIT AND FITTINGS SHALL BE SCHEDULE 40 PVC, HEAVY-WALL RIGID WITH SOLVENT-CEMENT-TYPE JOINTS AS RECOMMENDED BY THE MANUFACTURER.
- 5. -48 DC POWER COLOR CODE SHALL BE BLUE AND BLACK.
- B. WIRE AND CABLE:
- WIRE AND CABLE SHALL BE FLAME-RETARDANT, MDISTURE AND HEAT RESISTANT THERMOPLASTIC, SINGLE CONDUCTOR, COPPER, TYPE THHN/THWN, 600 VOLT, SIZES AS INDICATED, #12 AWG MINIMUM.
- 2. #10 AWG AND SMALLER CONDUCTORS SHALL BE SOLID AND #8 AWG AND LARGER CONDUCTORS SHALL BE STRANDED.
- 3. SOLDERLESS, PRESSURE-TYPE CONNECTORS CONSTRUCTED OF HIGH- STRENGTH, NON-CORRODIBLE, TIN-PLATED COPPER DESIGNED TO FURNISH HIGH- PULLOUT STRENGTH AND HIGH CONDUCTIVITY JOINTS SHALL BE USED.
- 4. SUPPORT GRIPS SHALL BE SINGLE WEAVE, CLOSED MESH, HIGH-GRADE, NON-MAGNETIC, TIN-COATED BRONZE CAPABLE OF SUPPORTING TEN TIMES THE CABLE DEAD WEIGHT, HUBBELL KELLEMS OR APPROVED EQUAL
- C. DISCONNECT SWITCHES:
- DISCONNECT SWITCHES SHALL BE HEAVY DUTY, DEAD-FRONT, QUICK-MAKE, QUICK-BREAK, EXTERNALLY OPERABLE, HANDLE LOCKABLE AND INTERLOCKED WITH COVER IN CLOSED POSITION, RATING AS INDICATED, UL LABELED FURNISHED IN NEMA 3R ENCLOSURE, SQUARE D CLASS 3110 OR APPROVED EQUAL
- D. SYSTEM GROUNDING:
- GROUNDING CONDUCTOR SHALL BE BARE, STRANDED, COPPER, SIZE AS INDICATED, EXCEPT ABOVE GROUND GROUNDING CONDUCTORS SHALL BE INSULATED.
- GROUND BUSSES SHALL BE BARE ANNEALED COPPER BARS OF RECTANGULAR CROSS SECTION. BUSS BARS SHALL BE TIN PLATED OR PAINTED GRAY AFTER CONNECTIONS HAVE BEEN COMPLETED.
- 3. CONNECTORS SHALL BE HIGH-CONDUCTIVITY, HEAVY DUTY, LISTED AND LABELED AS GROUNDING CONNECTORS FOR THE MATERIALS USED. USE TWO-HOLE COMPRESSION LUGS WITH HEAT SHRINK FOR MECHANICAL CONNECTIONS.
- 4. EXOTHERMIC WELDED CONNECTIONS SHALL BE PROVIDED IN KIT FORM AND SELECTED FOR THE SPECIFIC TYPES, SIZES, AND COMBINATIONS OF CONDUCTORS AND OTHER ITEMS TO BE CONNECTED.
- 5. GROUND RODS SHALL BE COPPER-CLAD STEEL WITH HIGH-STRENGTH STEEL CORE AND ELECTROLYTIC-GRADE COPPER OUTER SHEATH, MOLTEN WELDED TO CORE, 3/4" x 10'-0".

E. OTHER MATERIALS:

1. THE CONTRACTOR SHALL PROVIDE OTHER MATERIALS, THOUGH NOT SPECIFICALLY DESCRIBED, WHICH ARE REQUIRED FOR A COMPLETELY OPERATIONAL SYSTEM AND PROPER INSTALLATION OF THE WORK.





PART 3 EXECUTION

3.1 GENERAL:

- A ALL MATERIALS AND EQUIPMENT SHALL BE INSTALLED IN STRICT ACCORDANCE WITH THE MANUFACTURER'S RECOMMENDATIONS.
- B. EQUIPMENT SHALL BE TIGHTLY COVERED AND PROTECTED AGAINST DIRT OR WATER, AND AGAINST CHEMICAL OR MECHANICAL INJURY DURING INSTALLATION AND CONSTRUCTION PERIODS.
- 3.2 LABOR AND WORKMANSHIP:
- A. ALL LABOR FOR THE INSTALLATION OF MATERIALS AND EQUIPMENT FURNISHED FOR THE ELECTRICAL SYSTEM SHALL BE DONE BY EXPERIENCED MECHANICS OF THE PROPER TRADES.
- B. ALL ELECTRICAL EQUIPMENT FURNISHED SHALL BE ADJUSTED, ALIGNED AND TESTED BY THE CONTRACTOR AS REQUIRED TO PRODUCE THE INTENDED PERFORMANCE.
- C. UPON COMPLETION OF THE WORK, THE CONTRACTOR SHALL THOROUGHLY CLEAN ALL EXPOSED EQUIPMENT, REMOVE ALL LABELS AND ANY DEBRIS, CRATING OR CARTONS AND LEAVE THE INSTALLATION FINISHED AND READY FOR OPERATION.
- 3.3 COORDINATION:
- A THE CONTRACTOR SHALL COORDINATE THE INSTALLATION OF ELECTRICAL ITEMS WITH THE OWNER-FURNISHED EQUIPMENT DELIVERY SCHEDULE TO PREVENT UNNECESSARY DELAYS IN THE TOTAL WORK.
- 3.4. INSTALLATION:

A. CONDUIT:

- ALL ELECTRICAL WIRING SHALL BE INSTALLED IN CONDUIT AS HEREIN SPECIFIED. NO CONOUIT OR TUBING OF LESS THAN 3/4 INCH NOMINAL SIZE SHALL BE USED.
- 2. PROVIDE RGS CONDUIT FOR ALL EXPOSED, EXTERIOR CONDUIT.
- 3. PROVIDE SCHEDULE 40 PVC OR RGS CONDUIT BELOW GRADE, 1" MINIMUM, UNLESS NOTED OTHERWISE ALL 9D DEGREE BENDS TO ABOVE GRADE SHALL BE RGS. MINIMUM BURAL DEPTH SHALL BE 24" CLEAR TO TOP OF CONDUIT, UNLESS NOTED OTHERWISE.
- 4. USE GALVANIZED FLEXIBLE STEEL CONDUIT WHERE DIRECT CONNECTION IS NOT DESIRABLE FOR REASONS OF EQUIPMENT MOVEMENT, VIBRATION, OR FOR EASE OF MAINTENANCE. USE LIQUIDTIGHT, PVC COATED FLEXIBLE METAL CONDUIT FOR OUTDOOR APPLICATIONS.
- 5. INSTALL GALVANIZED FLEXIBLE STEEL CONDUIT AT ALL POINTS OF CONNECTION TO EQUIPMENT MOUNTED ON SUPPORTS TO ALLOW FOR EXPANSION AND CONTRACTION. NO MORE THAN 3' SEALTIGHT FROM RGS
- B. A RUN OF CONDUIT BETWEEN BOXES OR FITTINGS SHALL NOT CONTAIN MORE THAN THE EQUIVALENT OF FOUR QUARTER-BENDS INCLUDING THOSE BENDS LOCATED IMMEDIATELY AT THE BOX OR FITTING. THE RADIUS OF BENDS SHALL NEVER BE SHORTER THAN THAT OF THE CORRESPONDING TRADE ELBOW.
- WHERE CONDUIT HAS TO BE CUT IN THE FIELD, IT SHALL BE CUT SQUARE WITH A PIPE CUTTER USING CUTTING KNIVES.
- 8. ALL CONDUITS SHALL BE SWABBED CLEAN BY PULLING AN APPROPRIATE SIZE MANDREL THROUGH THE CONDUIT BEFORE INSTALLATION OF WIRE OR CABLE. CLEAR ALL BLOCKAGES AND REMOVE BURRS, DIRT, AND DEBRIS.
- INSTALL PULL STRINGS IN ALL EMPTY CONDUITS. IDENTIFY PULL STRINGS AT EACH END WITH IT'S DESTINATION.
- 10. PROVIDE INSULATED GROUNDING BUSHINGS FOR ALL CONDUITS STUBBED INTO EQUIPMENT ENCLOSURES OR STUBBED OUT FOR FUTURE USE BY OTHERS.
- 11. CONTRACTOR IS RESPONSIBLE FOR PROTECTING ALL CONDUITS DURING CONSTRUCTION, TEMPORARY OPENINGS IN THE CONOUIT SYSTEM SHALL BE PLUGGED OR CAPPED TO PREVENT ENTRANCE OF MOISTURE OR FOREIGN MATTER. CONTRACTOR SHALL REPLACE ANY CONDUITS CONTAINING FOREIGN MATERIALS THAT CANNOT BE REMOVED.
- 12. INSTALL 2" ORANGE DETECTABLE TAPE 12" ABOVE ALL UNDERGROUND CONDUIT AND WIRE
- CONDUITS SHALL BE INSTALLED IN SUCH A MANNER AS TO INSLIRE AGAINST COLLECTION OF TRAPPED CONDENSATION.

B. WIRE AND CABLE:

1. ALL POWER WIRING SHALL BE COLOR CODED AS FOLLOWS:

DESCRIPTION 120/2 PHASE A BLAC PHASE B RED PHASE C WHITE GROUND GREE	ek Black Red Blue E White	480Y/277V BROWN ORANGE YELLOW GRAY GREEN
--	------------------------------------	---

- 1-A DC -48 POWER COLOR CODE: BLUE & BLACK
- 2. SPUCES SHALL BE MADE ONLY AT OUTLETS, JUNCTION BOXES, OR ACCESSIBLE RACEWAYS WITH PRESSURE-TYPE CONNECTORS.
- 3. PULLING LUBRICANTS SHALL BE SOAPSTONE POWDER, POWDERED TALC, OR A COMMERCIAL PULLING COMPOUND. NO SOAP SUDS, SOAP FLAKES, OIL, DR GREASE SHALL BE USED, AS THESE MAY BE HARMFUL TO CABLE INSULATION. CONTRACTOR SHALL USE NYLON OR HEMP ROPE FOR PULLING CABLE TO

AVOID SCORING THE CONDUIT.

4. CABLES SHALL BE NEATLY TRAINED, WITHOUT INTERLACING, AND BE OF SUFFICIENT LENGTH IN ALL BOXES, EQUIPMENT, ETC. TO PERMIT MAKING A NEAT ARRANGEMENT. CABLES SHALL BE SECURED IN A MANNER TO AVOID TENSION ON CONDUCTORS OR TERMINALS, AND SHALL BE PROTECTED FROM MECHANICAL INJURY AND FROM MOISTURE. SHARP BENDS OVER CONDUIT BUSHINGS ARE PROHIBITED. DAMAGED CABLES SHALL BE REMOVED AND REPLACED AT THE CONTRACTOR'S EXPENSE.

C. DISCONNECT SWITCHES:

1. INSTALL DISCONNECT SWITCHES LEVEL AND PLUMB, CONNECT TO WIRING SYSTEM AND GROUND AS INDICATED.

D. GROUNDING:

- ALL METALLIC PARTS OF ELECTRICAL EQUIPMENT WHICH DO NOT CARRY CURRENT SHALL BE GROUNDED IN ACCORDANCE WITH THE REQUIREMENTS OF ARTICLE 250 OF THE NATIONAL ELECTRICAL CODE.
- PROVIDE ELECTRICAL GROUNDING AND BONDING SYSTEMS INDICATED WITH ASSEMBLY OF MATERIALS, INCLUDING GROUNDING ELECTRODES, BONDING JUMPERS ANO ADDITIONAL ACCESSORIES AS REOUIRED FOR A COMPLETE INSTALLATION.
- ROUTE GROUNDING CONNECTIONS AND CONDUCTORS TO GROUND IN THE SHORTEST AND STRAIGHTEST PATHS POSSIBLE TO MINIMIZE TRANSIENT VOLTAGE RISES.
- 4. TIGHTEN GROUNDING AND BONDING CONNECTORS, INCLUDING SCREWS AND BOLTS, IN ACCORDANCE WITH MANUFACTURER'S PUBLISHED TORQUE TIGHTENING VALUES FOR CONNECTORS AND BOLTS. WHERE MANUFACTURER'S TORQUING REQUIREMENTS ARE NOT AVAILABLE, TIGHTEN CONNECTIONS TO COMPLY WITH TIGHTENING TORQUE VALUES SPECIFIED IN UL 486A TO ASSURE PERMANENT ANO EFFECTIVE GROUNDING.
- ALL UNDERGROUND GROUNDING CONNECTIONS SHALL BE MADE BY THE EXOTHERWIC WELD PROCESS AND INSTALLED IN ACCORDANCE WITH THE MANUFACTURER'S INSTRUCTIONS.
- ALL GROUND CONNECTIONS SHALL BE INSPECTED FOR TIGHTNESS. EXOTHERMIC-WELDED CONNECTIONS SHALL BE APPROVED BY THE CONSTRUCTION INSPECTOR BEFORE BEING PERMANENTLY CONCEALED.
- APPLY CORROSION-RESISTANT FINISH TO FIELD CONNECTIONS, AND PLACES WHERE FACTORY APPLIED PROTECTIVE COATINGS HAVE BEEN DESTROYED. USE COPPER-BASED "NO-OX" OR APPROVED EQUAL.
- 8. A SEPARATE, CONTINUOUS, INSULATED EQUIPMENT GROUNDING CONDUCTOR SHALL BE INSTALLED IN ALL FEEDER AND BRANCH CIRCUITS
- 9. BOND ALL INSULATED GROUNDING BUSHINGS WITH A BARE #6 AWG GROUNDING CONDUCTOR TO A GROUND BUS OR GROUNDING LUG IN ENCLOSURE.
- DIRECT BURIED GROUND CONDUCTORS SHALL BE INSTALLED AT A NOMINAL DEPTH OF 3D* BELOW GRADE, UNLESS NOTED OTHERWISE.
- 11. ALL GROUNDING CONDUCTORS EMBEDDED IN OR PENETRATING CONCRETE SHALL BE INSULATED OR INSTALLED IN PVC CONDUIT.
- 12. INSTALL ELECTROLYTIC GROUNDING SYSTEM IN STRICT ACCORDANCE WITH MANUFACTURER'S INSTRUCTIONS. REMOVE SEALING TAPE FROM LEACHING AND BREATHER HOLES. INSTALL PROTECTIVE BOX FLUSH WITH GRADE.
- 13. DRIVE GROUND RODS UNTIL TOPS ARE 30 INCHES BELOW FINAL GRADE.
- 14. GROUNDING CONOUCTOR TO EQUIPMENT GROUND LUGS:
 - 1) BOLTED TO EQUIPMENT HOUSING WITH STAINLESS STEEL BOLTS AND
 - LOCK WASHERS. 2) ALL EQUIPMENT TO BE GROUNDED SHALL BE FREE OF PAINT OR ANY
 - OTHER MATERIAL COVERING BARE METAL AT THE POINT OF CONNECTION.

3.5 ACCEPTANCE TESTING:

- 1. PROVIDE PERSONNEL AND EQUIPMENT, MAKE REQUIRED TESTS, AND SUBMIT TEST REPORTS UPON COMPLETION OF TESTS.
- 2. WHEN MATERIAL AND/OR WORKMANSHIP IS FOUND NOT TO COMPLY WITH THE SPECIFIED REQUIREMENTS, THE NONCOMPLYING ITEMS SHALL BE REMOVED FROM THE JOBSITE AND REPLACED WITH ITEMS COMPLYING WITH THE SPECIFIED REQUIREMENTS PROMPTLY AFTER RECEIPT OF NOTICE OF SUCH NON-COMPLIANCE.

A TEST PROCEDURES:

1. ALL FEEDERS SHALL HAVE THEIR INSULATION TESTED AFTER INSTALLATION, BUT BEFORE CONNECTION TO DEVICES. THE CONDUCTORS SHALL TEST FREE FROM SHORT CIRCUITS AND GROUNDS. -TESTING SHALL BE FOR ONE MINUTE USING 1000V DC. INVESTIGATE ANY VALUES LESS THAN 50 MEGGHMS.


2. PRIOR TO ENERGIZING CIRCUITRY, TEST WIRING DEVICES FOR ELECTRICAL CONTINUITY AND PROPER POLARITY CONNECTIONS.

3. MEASURE AND RECORD VOLTAGES BETWEEN PHASES AND BETWEEN PHASE WIRES AND NEUTRALS, SUBMIT A REPORT OF MAXIMUM AND MINIMUM VOLTAGES.

4. PERFORM GROUND TEST TO MEASURE GROUND RESISTANCE OF GROUNDING SYSTEM USING THE IEEE STANDARD 3-POINT "FALL-OF-POTENTIAL" METHOD. PROVIDE PLOTTED TEST VALUES & LOCATION SKETCH. NOTIFY THE ENGINEER IMMEDIATELY IF MEASURED VALUE IS OVER 5 OHMS.

END OF SECTION

END OF SPECIFICATION





Local Official's Guide to RF



APPENDIX A

Optional Checklist for Determination Of Whether a Facility is Categorically Excluded

Filled out by Aaron Adelman of SMJ International 3/8

-1

of SMJ International o/b/o T-Mobile

continue

Optional Checklist for Local Government To Determine Whether a Facility is Categorically Excluded

Purpose: The FCC has determined that many wireless facilities are unlikely to cause human exposures in excess of RF exposure guidelines. Operators of those facilities are exempt from routinely having to determine their compliance. These facilities are termed "categorically excluded." Section 1.1307(b)(1) of the Commission's rules defines those categorically excluded facilities. This checklist will assist state and local government agencies in identifying those wireless facilities that are categorically excluded, and thus are highly unlikely to cause exposure in excess of the FCC's guidelines. Provision of the information identified on this checklist may also assist FCC staff in evaluating any inquiry regarding a facility's compliance with the RF exposure guidelines.

BACKGROUND INFORMATION
 Facility Operator's Legal Name: <u>T-Mobile</u> Facility Operator's Mailing Address: <u>2400 Westport Center Drive</u>
3. Facility Operator's Contact Name/Title: <u>Aaron Adelman, Authorized Agent</u>
5. Facility Operator's Fax:
7. Facility Address: 731 Spirit 40 Park Dr.
8. Facility City/Community: Chesterfield 9. Facility State and Zip Code: MO, 63005
10. Latitude: 38.67216882 11. Longitude: -90.6416901

Optional Local Government Checklist (page 2)

EVALUATION OF CATEGORICAL EXCLUSION
12. Licensed Radio Service (see attached Table 1): Cellular Radiotelephone Service
13. Structure Type (free-standing or building/roof-mounted): Free-standing
14. Antenna Type [omnidirectional or directional (includes sectored)]:
15. Height above ground of the lowest point of the antenna (in meters): <u>96'</u>
16. I Check if <u>all</u> of the following are true:
(a) This facility will be operated in the Multipoint Distribution Service, Paging and
Radiotelephone Service, Cellular Radiotelephone Service, Narrowband or Broadband
Personal Communications Service, Private Land Mobile Radio Services Paging
Operations, Private Land Mobile Radio Service Specialized Mobile Radio, Local
Multipoint Distribution Service, or service regulated under Part 74, Subpart I (see
question 12).
(b) This facility will not be mounted on a building (see question 13).
(c) The lowest point of the antenna will be at least 10 meters above the ground (see question
15).
If box 16 is checked, this facility is categorically excluded and is unlikely to cause exposure in
excess of the FCC's guidelines. The remainder of the checklist need not be completed. If box
16 is not checked, continue to question 17.
17. Enter the power threshold for categorical exclusion for this service from the attached Table 1
in watts ERP or EIRP* (note: EIRP = (1.64) X ERP):
18. Enter the total number of channels if this will be an omnidirectional antenna, or the
maximum number of channels in any sector if this will be a sectored antenna:
19. Enter the ERP or EIRP per channel (using the same units as in question 17):
20. Multiply answer 18 by answer 19:
21. Is the answer to question 20 less than or equal to the value from question 17 (yes or no)?
If the answer to question 21 is YES, this facility is categorically excluded. It is unlikely to cause
exposure in excess of the FCC's guidelines.
If the answer to question 21 is NO, this facility is not categorically excluded. Further
investigation may be appropriate to verify whether the facility may cause exposure in excess of the FCC's guidelines.

,

[&]quot;ERP" means "effective radiated power" and "EIRP" means "effective isotropic radiated power

TABLE 1: TRANSMITTERS, FACILITIES AND OPERATIONS SUBJECT TO ROUTINE ENVIRONMENTAL EVALUATION

	Los Marsa C Renning - mathilytonid2 sec. Renning - mathilytonid2 sec.
Experimental Radio Services (part 5)	power > 100 W ERP (164 W EIRP)
Multipoint Distribution Service (subpart K of part 21)	non-building-mounted antennas: height above ground level to lowest point of antenna < 10 m and power > 1640 W EIRP building-mounted antennas: power > 1640 W EIRP
Paging and Radiotelephone Service (subpart E of part 22)	non-building-mounted antennas: height above ground level to lowest point of antenna < 10 m and power > 1000 W ERP (1640 W EIRP) building-mounted antennas: power > 1000 W ERP (1640 W EIRP)
Cellular Radiotelephone Service (subpart H of part 22)	non-building-mounted antennas: height above ground level to lowest point of antenna < 10 m and total power of all channels > 1000 W ERP (1640 W EIRP) building-mounted antennas: total power of all channels > 1000 W ERP (1640 W EIRP)

.

TABLE 1 (cont.)


	A DUATION RECORDED IN THE SECOND
Personal Communications Services (part 24)	 (1) Narrowband PCS (subpart D): <u>non-building-mounted antennas</u>: height above ground level to lowest point of antenna < 10 m and total power of all channels > 1000 W ERP (1640 W EIRP) <u>building-mounted antennas</u>: total power of all channels > 1000 W ERP (1640 W EIRP) (2) Broadband PCS (subpart E):
	non-building-mounted antennas: height above ground level to lowest point of antenna < 10 m and total power of all channels > 2000 W ERP (3280 W EIRP) building-mounted antennas: total power of all channels > 2000 W ERP (3280 W EIRP)
Satellite Communications (part 25)	all included
General Wireless Communications Service (part 26)	total power of all channels > 1640 W EIRP
Wireless Communications Service (part 27)	total power of all channels > 1640 W EIRP
Radio Broadcast Services (part 73)	all included

TABLE 1 (cont.)

	A 20 STREED REPORTED AS STR
Experimental, auxiliary, and special broadcast and other program distributional services (part 74)	subparts A, G, L: power > 100 W ERP subpart I: <u>non-building-mounted antennas</u> : height above ground level to lowest point of antenna < 10 m <u>and power > 1640 W EIRP</u> <u>building-mounted antennas</u> : power > 1640 W EIRP
Stations in the Maritime Services (part 80)	ship earth stations only
Private Land Mobile Radio Services Paging Operations (part 90)	<u>non-building-mounted antennas</u> : height above ground level to lowest point of antenna < 10 m <u>and power</u> > 1000 W ERP (1640 W EIRP) <u>building-mounted antennas</u> : power > 1000 W ERP (1640 W EIRP)
Private Land Mobile Radio Services Specialized Mobile Radio (part 90)	non-building-mounted antennas: height above ground level to lowest point of antenna < 10 m and total power of all channels > 1000 W ERP (1640 W EIRP) building-mounted antennas: total power of all channels > 1000 W ERP (1640 W EIRP)

TABLE 1 (cont.)

	interest in the state of the st
Amateur Radio Service (part 97)	transmitter output power > levels specified in § 97.13(c)(1) of this chapter
Local Multipoint Distribution Service (subpart L of part 101)	non-building-mounted antennas: height above ground level to lowest point of antenna < 10 m and power > 1640 W EIRP building-mounted antennas: power > 1640 W EIRP
	LMDS licensees are required to attach a label to subscriber transceiver antennas that: (1) provides adequate notice regarding potential radiofrequency safety hazards, <i>e.g.</i> , information regarding the safe minimum separation distance required between users and transceiver antennas; and (2) references the applicable FCC-adopted limits for radiofrequency exposure specified in § 1.1310 of this chapter.



P LEGEND	5	
$\begin{array}{c ccccccccccccccccccccccccccccccccccc$	DATE	
Import RD CALCULATED POINT POB = POINT OF BEGINNING PB 337, PC = POINT OF COMMENCEMENT PB 337, PC = STANTON POC = POINT OF COMMENCEMENT PRECORDED INFORMATION PRECORDED INFORMATION<td>REVISION</td><td></td>	REVISION	
Asbuilt Tower Survey, made on the ground under the supervision of a rsed Professional Engineer. Date of field survey is May 20, 2009. Ing surveying Instruments were used at lime of field visit; Nikon NPL-352, Reflectoriess and Hiper + Legacy E RTK, GO 1HZ. are based on Missouri East State Plane Coordinates NAD 83 by GPS	REM	
round utilities, underground encroochments or building toundations were lacated as a part of this survey, unless otherwise shawn. Trees and shrubs unless atherwise shawn. « used is a Continuously Operating Reference Station, PID DH4182. Onsite « as shawn herean, Elevalians shawn are in feet and refer to NAVD B8. y was conducted for the purpose of an Asbuilt Tawer Survey anly, and is to delineal the regulatory jurisdiction of any federal, raglonal or locat	9 PR	OJECT NO. 09-0266
f, commission or other similar entity. a directed to the foct that this survey may have been reduced or enlarged a repraduction. This should be taken into consideration when abtaining scaled y was conducted without the benefit of an Abstract Title search. erceby states the Geodetic Coordinates and the elevation shown for the terline of the tawer are occurate to within +/- 15 feet harizontally and to i feet vertically (FAA Accuracy Code 1A).	DRAWN BY: DCP CHECKED RY: AAK	PELD CREW: WS APPROVED BY: WH DATE: 06/10/09 SCALE: 1* = 20' SHEET 1 OF 2
for a Class "A" Survey. by you which this map or plot is based has a clasure precision of not tess to 15,000 feet (1::5,000) and an angular error that does not exceed 10 a the square root of the number of angles turned. Field traverse was not ery is not valid without the ariginal signature and the ariginal seal of a state ery is not valid without the ariginal signature and the ariginal seal of a state ery is not valid without the ariginal signature and the ariginal seal of a state ery does not constitute a complete boundary survey of the Porent Tract. on aur field work and research, the lease porcel has access to Spirit 40 public right-ol-way) by means of the occess cosement shown in this easement area lies entitlely within the parent tract. No accements or other i porties disclosed by our research preclude access over the parent tract zon Wiretess tease parcel to Spirit 40 Park Drive (the public right-ol-way). If was canducted with reference to a prior survey prepared by Kuthmann Inc., Michael S. Huber PLS, LS No. 2491, Project No. 990325-0005, dated 1000. Initial structures exist, at time of survey, within one-half $(1-1/2)$ miles of unicotions lower. E atting only, the subject property appears to lie in Zone "Shaded X" of the ter Role Map Community Ponel No. 2916300120H, which bears on stifective at 2, 1985 and IS in a special fload hazard area. and USD in A special fload hazard area. and IS in a special fload hazard area. as of less than one foot ar with drainage areas of tess than one square bas protected by levees from 100-year fload.	ASBUILT TOWER SURVEY	T-MOBILE CENTRAL, LLC 2001 BOTHERFED READ, SUT 51900
E Planned Industrial District nunicolians Tower	_	
Alions are subject to for further Zoning Information et O. Geisel, Director of Public Works of the City of issouri (65) 537-4749. RECEIVED AUG 1 2 2009 PT. OF PLANNING PUBLIC WORKS	SMW Engineering Group, Inc.	RIMO BROUP, INC. 205-252-6985 RIMO BROUP, INC. WW.Smweng.com
SPIRIT 40 PARK MO06205A US SURVEY 122, T-45-N, R-3-E ST. LOUIS COUNTY, MISSOURI	Contraction and the	ENGINEER